



# International Impex Trade Ltd.

Hong Kong, Unit 04, 7/F Bright Way Tower NO.33 Mong Kok RD KL


Skype: inga.impex Phone: +852 81975533 – we speak Russian

ICQ: 121401019 Phone: +852 81912393 – we speak Russian, Spanish, English, French


e-mail: inga@impexcn.com

## AHD DVR Price List


| 4-Channel H.264 Stand-alone AHD DVR                   |                     |                     |   |   |
|---|---------------------|---------------------|---|---|
| Item No.  | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture   | Specifications  |
| AHD-KS604   | \$30                | \$28                |  <p>Color: White or Black</p> | ◇4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)   |
|   |                     |                     |   | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|   |                     |                     |   | ◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024  |
|   |                     |                     |   | ◇Audio input/output: RCA 2-channel input/ RCA 1-channel output  |
|   |                     |                     |   | ◇Display resolution: 720P/960H  |
|   |                     |                     |   | ◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)  |
|   |                     |                     |   | ◇Recording resolution: 720P/960H, real time   |
|   |                     |                     |   | ◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)  |
|   |                     |                     |   | ◇Playback resolution: 4 x 720P  |
|   |                     |                     |   | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|   |                     |                     |   | ◇ 2 × USB, 1× USB Mouse, 1 × IR Controller  |
|   |                     |                     |   | ◇Backup: USB2.0 and Network, Multi-language menu  |
|   |                     |                     |   | ◇Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback  |
|   |                     |                     |   | ◇Support 1 SATA 2.5/3.5" Hard Disk interface (4TB in total)   |
| ◇Standard Color: White Optional color: Black for free |                     |                     |   |   |
| ◇Dimension: 215*215*53 (LxWxH) Weight:2.0Kg           |                     |                     |   |   |
| Item No.  | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture   | Specifications  |


|           |      |      |  |  |
|-----------|------|------|--|--|
| AHD-KM604 | \$30 | \$28 |  <p style="text-align: center;"><b>4CH × 720P</b></p> <p style="text-align: center;"><b>Color: White or Black</b></p> | <p>◇<b>4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)</b></p> <p>◇Video Compression: H.264; Video System: PAL/NTSC</p> <p>◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024</p> <p>◇Audio input/output: RCA 2-channel input/ RCA 1-channel output</p> <p>◇Display resolution: 720P/960H</p> <p>◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)</p> <p>◇Recording resolution: 720P/960H, real time</p> <p>◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)</p> <p>◇Playback resolution: 4 x 720P</p> <p>◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry</p> <p>◇ 2 × USB, 1× USB Mouse, 1 × IR Controller</p> <p>◇Backup: USB2.0 and Network, Multi-language menu</p> <p>◇Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback</p> <p>◇Support 1 SATA 2.5/3.5" Hard Disk interface (4TB in total)</p> <p>◇Standard Color: White Optional color: Black</p> <p>◇Dimension: 206*206*51 (LxWxH) Weight:2.0Kg</p> |
|-----------|------|------|--|--|




| Item No.  | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture   | Specifications  |
|-----------|---------------------|---------------------|---|---|
| AHD-KL604 | \$30                | \$28                |  <p style="text-align: center;"><b>NEW</b></p> <p style="text-align: center;"><b>4CH × 720P</b></p> | <p>◇<b>4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)</b></p> <p>◇Video Compression: H.264; Video System: PAL/NTSC</p> <p>◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024</p> <p>◇Audio input/output: RCA 2-channel input/ RCA 1-channel output</p> <p>◇Display resolution: 720P/960H</p> <p>◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)</p> <p>◇Recording resolution: 720P/960H, real time</p> <p>◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)</p> <p>◇Playback resolution: 4 x 720P</p> <p>◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry</p> <p>◇ 2 × USB, 1× USB Mouse, 1 × IR Controller</p> <p>◇Backup: USB2.0 and Network, Multi-language menu</p> <p>◇Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback</p> <p>◇Support 1 SATA 2.5/3.5" Hard Disk interface (4TB in total)</p> <p>◇Multi-languages</p> |

◇Dimension: 215x215x49mm (LxWxH) Weight:2.0Kg


| Item No.   | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications  |
|--|---------------------|---------------------|--|---|
| AHD-R604   | \$38                | \$36                |  | ◇4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)   |
|  |                     |                     |  | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|  |                     |                     |  | ◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|  |                     |                     |  | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|  |                     |                     |  | ◇Display resolution: 720P/960H  |
|  |                     |                     |  | ◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)  |
|  |                     |                     |  | ◇Recording resolution: 720P/960H, real time   |
|  |                     |                     |  | ◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)  |
|  |                     |                     |  | ◇Playback resolution: 4 x 720P  |
|  |                     |                     |  | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|  |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|  |                     |                     |  | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|  |                     |                     |  | ◇Multi-language menu  |
| ◇Support PELCO-P&PELCO-D PTZ control               |                     |                     |  |   |
| ◇Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |  |   |
| ◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg      |                     |                     |  |   |


| Item No.   | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications  |
|--|---------------------|---------------------|--|---|
| AHD-C604   | \$38                | \$36                |  | ◇4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)   |
|  |                     |                     |  | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|  |                     |                     |  | ◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|  |                     |                     |  | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|  |                     |                     |  | ◇Display resolution: 720P/960H  |
|  |                     |                     |  | ◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)  |
|  |                     |                     |  | ◇Recording resolution: 720P/960H, real time   |
|  |                     |                     |  | ◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)  |
|  |                     |                     |  | ◇Playback resolution: 4 x 720P  |
|  |                     |                     |  | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|  |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|  |                     |                     |  | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|  |                     |                     |  | ◇Support PELCO-P&PELCO-D PTZ control  |
| ◇Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |  |   |
| ◇Multi-language menu                               |                     |                     |  |   |

◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg

| 8-Channel H.264 Stand-alone AHD DVR           |                     |                     |  |   |
|---|---------------------|---------------------|--|---|
| Item No.                                      | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications  |
| <b>AHD-K604</b>                               | <b>\$38</b>         | <b>\$36</b>         | <div style="text-align: center;"> <p style="color: green; font-weight: bold; font-size: 1.2em;">4CH × 720P</p>  </div> | ◇ <b>4-Channel H.264 Network Digital Video Recorder (4CH × 720P/960H)</b>   |
|   |                     |                     |  | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|   |                     |                     |  | ◇Video input/output: BNC 4-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|   |                     |                     |  | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|   |                     |                     |  | ◇Display resolution: 720P/960H  |
|   |                     |                     |  | ◇Display frame rate: 100fps(PAL);120fps (NTSC) (shared by 4 cameras)  |
|   |                     |                     |  | ◇Recording resolution: 720P/960H, real time   |
|   |                     |                     |  | ◇Recording frame rate: 720P@100fps/960H@100fps(PAL); 720P@120fps/960H@120fps(NTSC)  |
|   |                     |                     |  | ◇Playback resolution: 4 x 720P  |
|   |                     |                     |  | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|   |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|   |                     |                     |  | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|   |                     |                     |  | ◇Support PELCO-P&PELCO-D PTZ control, Multi-language menu   |
|   |                     |                     |  | ◇Support 2 SATA Hard Disk interface (8TB in total)  |
| ◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg |                     |                     |  |   |



### 8-Channel H.264 Stand-alone AHD DVR

| Item No.   | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications  |
|--|---------------------|---------------------|--|---|
| <b>AHD-R708</b>                                    | <b>\$55</b>         | <b>\$53</b>         | <div style="text-align: center;"> <p style="color: green; font-weight: bold; font-size: 1.2em;">NEW</p> <p style="color: green; font-weight: bold; font-size: 1.2em;">8CH × 720P</p>  </div> | ◇ <b>8-Channel H.264 Network Digital Video Recorder (8CH ×720P/960H)</b>  |
|  |                     |                     |  | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|  |                     |                     |  | ◇Video input/output: BNC 8-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|  |                     |                     |  | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|  |                     |                     |  | ◇Alarm input/output: 4-channel input/1-channel output   |
|  |                     |                     |  | ◇Display resolution: 720P/960H  |
|  |                     |                     |  | ◇Display frame rate: 200fps(PAL);240fps (NTSC) (shared by 8 cameras)  |
|  |                     |                     |  | ◇Recording resolution: 720P/960H, Real Time   |
|  |                     |                     |  | ◇Recording frame rate: 720P@200fps/960H@200fps(PAL); 720P@240fps/960H@240fps(NTSC)  |
|  |                     |                     |  | ◇Playback resolution: 4 x 720P  |
|  |                     |                     |  | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|  |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|  |                     |                     |  | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|  |                     |                     |  | ◇Support PELCO-P&PELCO-D PTZ control  |
| ◇Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |  |   |
| ◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg      |                     |                     |  |   |


| Item No.   | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture   | Specifications  |
|--|---------------------|---------------------|---|---|
| <b>AHD-C708</b>                                    | <b>\$55</b>         | <b>\$53</b>         |  <p style="text-align: center;"><b>8CH × 720P</b></p> | ◇ <b>8-Channel H.264 Network Digital Video Recorder (8CH ×720P/960H)</b>  |
|  |                     |                     |   | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|  |                     |                     |   | ◇Video input/output: BNC 8-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|  |                     |                     |   | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|  |                     |                     |   | ◇Alarm input/output: 4-channel input/1-channel output   |
|  |                     |                     |   | ◇Display resolution: 720P/960H  |
|  |                     |                     |   | ◇Display frame rate: 200fps(PAL);240fps (NTSC) (shared by 8 cameras)  |
|  |                     |                     |   | ◇Recording resolution: 720P/960H, Real Time   |
|  |                     |                     |   | ◇Recording frame rate: 720P@200fps/960H@200fps(PAL); 720P@240fps/960H@240fps(NTSC)  |
|  |                     |                     |   | ◇Playback resolution: 4 x 720P  |
|  |                     |                     |   | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|  |                     |                     |   | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|  |                     |                     |   | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|  |                     |                     |   | ◇Support PELCO-P&PELCO-D PTZ control  |
| ◇Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |   |   |
| ◇Multi-language menu                               |                     |                     |   |   |
| ◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg      |                     |                     |   |   |

| Item No.   | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture   | Specifications  |
|--|---------------------|---------------------|---|---|
| <b>AHD-K708</b>                                    | <b>\$55</b>         | <b>\$53</b>         |  <p style="text-align: center;"><b>8CH × 720P</b></p> | ◇ <b>8-Channel H.264 Network Digital Video Recorder (8CH ×720P/960H)</b>  |
|  |                     |                     |   | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|  |                     |                     |   | ◇Video input/output: BNC 8-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024 ,1-channel HDMI output                                 |
|  |                     |                     |   | ◇Audio input/output: RCA 4-channel input/ RCA 1-channel output /RCA 1-channel line input  |
|  |                     |                     |   | ◇Alarm input/output: 4-channel input/1-channel output   |
|  |                     |                     |   | ◇Display resolution: 720P/960H  |
|  |                     |                     |   | ◇Display frame rate: 200fps(PAL);240fps (NTSC) (shared by 8 cameras)  |
|  |                     |                     |   | ◇Recording resolution: 720P/960H, Real Time   |
|  |                     |                     |   | ◇Recording frame rate: 720P@200fps/960H@200fps(PAL); 720P@240fps/960H@240fps(NTSC)  |
|  |                     |                     |   | ◇Playback resolution: 4 x 720P  |
|  |                     |                     |   | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|  |                     |                     |   | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|  |                     |                     |   | ◇With RS485 x 1,1 × IR Controller ,2× USB2.0, 1 × USB2.0 mouse  |
|  |                     |                     |   | ◇Support PELCO-P&PELCO-D PTZ control  |
| ◇Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |   |   |
| ◇Multi-language menu                               |                     |                     |   |   |
| ◇Dimension: 354x245x45mm (LxWxH) Weight:4.0Kg      |                     |                     |   |   |

# 16-Channel H.264 Stand-alone AHD DVR

| Item No.  | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications   |
|---|---------------------|---------------------|--|--|
| <b>AHD-L816</b>                                     | <b>\$106</b>        | <b>\$104</b>        |    | ◇ <b>16-Channel H.264 Network Digital Video Recorder ( 16CH × 720P/960H)</b>   |
|   |                     |                     |  | ◇ Video Compression: H.264; Video System: PAL/NTSC   |
|   |                     |                     |  | ◇ Video input/output: BNC 16-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024; 1-channel <b>HDMI</b> output                         |
|   |                     |                     |  | ◇ Audio input/output: RCA 16-channel input/ RCA 1-channel output   |
|   |                     |                     |  | ◇ Alarm input/output: 4-channel input/1-channel output   |
|   |                     |                     |  | ◇ Display resolution: 720P/960H  |
|   |                     |                     |  | ◇ Display frame rate: 400fps(PAL);480fps (NTSC) (shared by 16 cameras)   |
|   |                     |                     |  | ◇ Recording resolution: 720P/960H, Real Time   |
|   |                     |                     |  | ◇ Recording frame rate: 720P/960H@400fps ( PAL); 720P/960H@480fps(NTSC)  |
|   |                     |                     |  | ◇ Playback resolution: 4 x 720P  |
|   |                     |                     |  | ◇ RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|   |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS  |
|   |                     |                     |  | ◇ With RS422 x 1, 1 × USB 2.0, 1 × IR Controller , 1× USB2.0 mouse   |
|   |                     |                     |  | ◇ Support PELCO-P&PELCO-D PTZ control  |
| ◇ Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |  |  |
| ◇ Multi-language menu                               |                     |                     |  |  |
| ◇ Dimension: 405mm×325mm×65mm (LxWxH) Weight:6.0Kg  |                     |                     |  |  |
| <b>AHD-N816</b>                                     | <b>\$106</b>        | <b>\$104</b>        |  | ◇ <b>16-Channel H.264 Network Digital Video Recorder ( 16CH × 720P/960H)</b>   |
|   |                     |                     |  | ◇ Video Compression: H.264; Video System: PAL/NTSC   |
|   |                     |                     |  | ◇ Video input/output: BNC 16-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024; 1-channel <b>HDMI</b> output                         |
|   |                     |                     |  | ◇ Audio input/output: RCA 16-channel input/ RCA 1-channel output   |
|   |                     |                     |  | ◇ Alarm input/output: 4-channel input/1-channel output   |
|   |                     |                     |  | ◇ Display resolution: 720P/960H  |
|   |                     |                     |  | ◇ Display frame rate: 400fps(PAL);480fps (NTSC) (shared by 16 cameras)   |
|   |                     |                     |  | ◇ Recording resolution: 720P/960H, Real Time   |
|   |                     |                     |  | ◇ Recording frame rate: 720P/960H@400fps ( PAL); 720P/7960H@480fps(NTSC)   |
|   |                     |                     |  | ◇ Playback resolution: 4 x 720P  |
|   |                     |                     |  | ◇ RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|   |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS  |
|   |                     |                     |  | ◇ With RS422 x 1, 1 × USB 2.0, 1 × IR Controller , 1× USB2.0 mouse   |
|   |                     |                     |  | ◇ Support PELCO-P&PELCO-D PTZ control ◇ Multi-language menu  |
| ◇ Support 2 SATA Hard Disk interface (8TB in total) |                     |                     |  |  |
| ◇ Dimension: 405mm×330mm×65mm (LxWxH) Weight:6.0Kg  |                     |                     |  |  |



| Item No.  | Unit Price (<20PCS) | Unit Price (≥20PCS) | Picture  | Specifications  |
|---|---------------------|---------------------|--|---|
| <b>AHD-V816</b>                                   | <b>\$106</b>        | <b>\$104</b>        |  | ◇ <b>16-Channel H.264 Network Digital Video Recorder ( 16CH × 720P/960H)</b>  |
|   |                     |                     |  | ◇Video Compression: H.264; Video System: PAL/NTSC   |
|   |                     |                     |  | ◇Video input/output: BNC 16-channel Input and 1-channel BNC Output and 1-channel VGA Output; VGA Resolution: 1024x768,1280x1024; 1-channel <b>HDMI</b> output                         |
|   |                     |                     |  | ◇Audio input/output: RCA 16-channel input/ RCA 1-channel output   |
|   |                     |                     |  | ◇Alarm input/output: 4-channel input/1-channel output   |
|   |                     |                     |  | ◇Display resolution: 720P/960H  |
|   |                     |                     |  | ◇Display frame rate: 400fps(PAL);480fps (NTSC) (shared by 16 cameras)   |
|   |                     |                     |  | ◇Recording resolution: 720P/960H, Real Time   |
|   |                     |                     |  | ◇Recording frame rate: 720P/960H@400fps ( PAL); 720P/7960H@480fps(NTSC)   |
|   |                     |                     |  | ◇Playback resolution: 4 x 720P  |
|   |                     |                     |  | ◇RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , P2P, Support Internet Explorer and special client software, Support remote view by Iphone/Windows/Andriod/Symbian/Blackberry |
|   |                     |                     |  | ◇ Support Internet Explorer, Mobile phone(Iphone/Windows/Andriod/Symbian/Blackberry), and CMS   |
|   |                     |                     |  | ◇With RS422 x 1, 1 × USB 2.0, 1 × IR Controller , 1× USB2.0 mouse   |
|   |                     |                     |  | ◇Support PELCO-P&PELCO-D PTZ control  |
|   |                     |                     |  | ◇Support 2 SATA Hard Disk interface (8TB in total)  |
| ◇Multi-language menu                              |                     |                     |  |   |
| ◇Dimension: 405mm×330mm×65mm (LxWxH) Weight:6.0Kg |                     |                     |  |   |

**Note: All DVRs include the Languages: English, German, Russian, French, Portuguese, Spanish, Italian, Polish, Hungarian, Slovak, Vietnamese, Greek, Japanese**

**Trade Terms:**

- 1. Price Term: Ex-Factory, Shenzhen, China**
- 2. Payment Term: T/T or West Union**
- 3. Samples: Available after customers pay the charges of sample & freight fees**
- 4. Minimum Order Quantity: At least 10pcs/model after sample order**
- 5. Lead time: 7-15 days**
- 6. Warranty: One Year after shipment date**