



International Impex Trade Ltd.

Hong Kong, Unit 04, 7/F Bright Way Tower NO.33 Mong Kok RD KL

Skype: inga.impex Phone: +852 81975533 – we speak Russian



ICQ: 121401019 Phone: +852 81912393 – we speak Russian, Spanish, English, French



e-mail: inga@impexcn.com

Speed Dome Cameras Price



(IP & Analog)

HD-IP P2P Speed Dome Cameras				
Picture	Item No.	Unit Price USD	Specification	Remarks
 4.5", 10X, High Speed, IR, IPC	ITP-013AH10XT	154	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	4.5" Mini HD-IP High Speed Dome Camera Weatherproof Outdoor IP66 ∅ 16x6PCS IR LEDs, IR Range: 50m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 0.02°-200°/sec; Tilt Speed: 0.02°-120°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu: Multiple Language Power Consumption: ≤ 15W, DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs 
	ITP-020AH10XT	165	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	
 4.5", 10X, High Speed, IR, IPC	ITP-013BH10XT	154	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	4.5" Mini HD-IP High Speed Dome Camera Weatherproof Outdoor IP66 ∅ 16x8PCS IR LEDs, IR Range: 50m Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip Pan Speed: 200°/sec; Tilt Speed: 100°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Protocol TCP/IP, HTTP, FTP, RTSP Support OSD Menu Available Power Consumption: ≤ 20W, DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs 
	ITP-020BH10XT	165	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	
 4.5", 10X, High Speed, IPC	ITP-013DH10XT	148	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	4.5" Mini HD-IP High Speed Dome Camera Weatherproof Outdoor IP66 Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 0.02°-200°/sec; Tilt Speed: 0.02°-120°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu: Multiple Language Power Consumption: ≤ 15W, DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs 
	ITP-020DH10XT	158	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 10X Optical Zoom (f=5mm-50mm)	
 7", 18X/22X, Medium Speed, IR, IPC	ITP-013AM18XT	168	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 18X Optical Zoom (f=4.7mm-84.6mm)	7" HD-IP Medium Speed Dome Camera Weatherproof Outdoor IP66 ∅ 22x8PCS IR LEDs, IR Range: 120m Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip Pan Speed: 60°/sec; Tilt Speed: 45°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Protocol TCP/IP, HTTP, FTP, RTSP OSD Menu Available Power Consumption: ≤ 20W, DC12V/4A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 32x32x43(cm) Weight: 7Kgs 
	ITP-020AM22XT	179	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 22X Optical Zoom (f=3.9mm-85.5mm)	

 <p>7", 18X/22X, Medium Speed, IR, IPC</p>	ITP-013BM18XT	168	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 18X Optical Zoom (f=4.7mm-84.6mm)	7" HD-IP Medium Speed Dome Camera Weatherproof Outdoor IP66 ø 22x8PCS+ ø 16x6PCS IR LEDs, IR Range: 120m Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip Pan Speed: 60°/sec; Tilt Speed: 45°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Protocol TCP/IP, HTTP, FTP, RTSP Support OSD Menu Available Power Consumption: ≤ 20W, DC12V/4A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 32x32x43(cm) Weight: 7Kgs
	ITP-020BM22XT	179	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 22X Optical Zoom (f=3.9mm-85.5mm)	


 <p>7", 18X/22X, High Speed, IR, IPC</p>	ITP-013BH18XT	182	1/3" Aptina Low Illumination 1.3MP CMOS Sensor, TI DaVinci™ DM365, Main Stream: 720P@30fps; With IR-CUT 18X Optical Zoom (f=4.7mm-84.6mm)	7" HD-IP High Speed Dome Camera Weatherproof Outdoor IP66 ø 22x8PCS+ ø 16x6PCS IR LEDs, IR Range: 120m Pan Range: 0°~360° Continue; Tilt Range: 0°~90° Flip Pan Speed: 200°/sec; Tilt Speed: 100°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Protocol TCP/IP, HTTP, FTP, RTSP Support OSD Menu Available Power Consumption: ≤ 20W, DC12V/4A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 32x32x43(cm) Weight: 7Kgs
	ITP-020BH22XT	193	1/2.7" OmniVision Low Illumination 2MP CMOS Sensor, TI DaVinci™ DM368, Main Stream: 1080P@30fps; With IR-CUT 22X Optical Zoom (f=3.9mm-85.5mm)	

AHD-Analog Speed Dome Cameras



Picture	Item No.	Unit Price USD	Specification	Remarks
 <p>4.5", 10X, High Speed, IR AHD</p>	IPA-013AH10XD	158	1/3" SONY CMOS Sensor 1.4MP/720P/960P Low Illumination, ICR, 3D NR, Digital Zoom 10X Optical Zoom (f=5.1mm-51mm)	4.5" HD-AHD Mini High Speed Dome Camera Weatherproof Outdoor IP66 ø 16x6PCS IR LEDs, IR Range: 60m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 200°/sec; Tilt Speed: 80°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu Available Power Adaptor: DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs
 <p>7", 18X, Medium Speed, IR, AHD</p>	IPA-013BM18XD	180	1/3" Aptina CMOS Sensor 1.3MP/720P/960P Low Illumination, ICR, 3D NR, Digital Zoom 18X Optical Zoom (f=4.7mm-84.6mm)	7" HD-AHD Medium Speed Dome Camera Weatherproof Outdoor IP66 ø 22x8PCS+ ø 16x6PCS IR LEDs, IR Range: 120m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 60°/sec; Tilt Speed: 45°/sec Preset Points: 220 Guard Tours: 4 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu Available Power Adaptor: DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 32x32x43(mm) Weight: 7Kgs
 <p>7", 18X, High Speed, IR, AHD</p>	IPA-013CH18XD	255	1/3" Aptina CMOS Sensor 1.3MP/720P/960P Low Illumination, ICR, 3D NR, Digital Zoom 18X Optical Zoom (f=4.7mm-84.6mm)	7" HD-AHD Medium Speed Dome Camera Weatherproof Outdoor IP66 ø 22x8PCS+ ø 16x6PCS IR LEDs, IR Range: 120m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 60°/sec; Tilt Speed: 45°/sec Preset Points: 220 Guard Tours: 4 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu Available Power Adaptor: DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 32x32x43(mm) Weight: 7Kgs

Analog Speed Dome Cameras

Picture	Item No.	Unit Price USD	Specification	Remarks
 <p>4.5", 10X, High Speed, IR</p>	ISD-AH10X	119	1/3" Super HAD II SONY CCD, Effio 10X Optical Zoom (f=5mm-50mm) Color 650TVL, Black 700TVL	4.5" Mini High Speed Dome Camera (Analog) Weatherproof Outdoor IP66 Ø 16x6PCS IR LEDs, IR Range: 50m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 0.02°~200°/sec; Tilt Speed: 0.02°~120°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu: Multiple Language Power Consumption: ≤ 15W, DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs
 <p>4.5", 10X, High Speed, IR</p>	ISD-BH10X	119	1/3" Super HAD II SONY CCD, Effio 10X Optical Zoom (f=5mm-50mm) Color 650TVL, Black 700TVL	4.5" Mini High Speed Dome Camera (Analog) Weatherproof Outdoor IP66 Ø 16x8PCS IR LEDs, IR Range: 50m Pan Range: 0°~360° Continue; Tilt Range: 0°~93° Flip Pan Speed: 0.02°~200°/sec; Tilt Speed: 0.02°~120°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported OSD Menu: Multiple Language Power Consumption: ≤ 15W, DC12V/3A Lightning Protection: Transient Voltage 6000V Size of Package (LxWxH): 28x32x20(cm) Weight: 3.4Kgs
 <p>6", 22X, Medium Speed, IR</p>	ISD-AM22X	132	1/3" Super HAD II SONY CCD, Effio 22X Optical Zoom (f=3.9mm-85.5mm) Color 650TVL, Black 700TVL	6" Medium Speed Dome Camera (Analog) Weatherproof Outdoor IP66 Ø 20x6PCS+ Ø 16x5PCS IR LEDs, IR Range: 100m Pan Range: 0°~360° Continue; Tilt Range: 0°~94° Flip Pan Speed: 60°/sec; Tilt Speed: 45°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported Power Consumption: ≤ 20W, DC12V/4A Lightning Protection: Transient Voltage 3000V Size of Package (LxWxH): 28x28x42(cm) Weight: 3.8Kgs
 <p>6", 22X, Medium Speed, IR</p>	ISD-AH22X	152	1/3" Super HAD II SONY CCD, Effio 22X Optical Zoom (f=3.9mm-85.5mm) Color 650TVL, Black 700TVL	6" High Speed Dome Camera (Analog) Weatherproof Outdoor IP66 Ø 20x6PCS+ Ø 16x5PCS IR LEDs, IR Range: 100m Pan Range: 0°~360° Continue; Tilt Range: 0°~94° Flip Pan Speed: 0.02°~200°/sec; Tilt Speed: 100°/sec Preset Points: 220 Guard Tours: 3 Groups Guard Points: Max.16 points RS485, Pelco D/P supported Power Consumption: ≤ 20W, DC12V/4A Lightning Protection: Transient Voltage 3000V Size of Package (LxWxH): 28x28x42(mm) Weight: 3.8Kgs
	ISD-EAD1	106	1/3" Super HAD II Sony Color CCD, Effio-E, 12X(f=5~60mm), Color 650TVL, Black 700TVL	Vandalproof Mini Speed Dome camera Pan range: 0°~360° Continue (Not 355°) Tilt range: 0°~90° Flip Pan Speed: Max 80°/sec Preset: 16 Weatherproof Outdoor IP66 RS485, Pelco D/P supported Size: Ø121x177mm Weight: 3.0Kg

	ISD-EAP1	106	1/3" Super HAD II Sony Color CCD, Effio-E, 12X(f=5~60mm), Color 650TVL, Black 700TVL	Vandalproof Mini Speed Dome camera Pan range: 0°~360° Continue (Not 355°) Tilt range: 0°~90° Flip Pan Speed: Max 80°/sec Preset: 16 Weatherproof Outdoor IP66 RS485, Pelco D/P supported Size: Ø138x212mm Weight: 3.0Kg
--	-----------------	------------	--	---

PTZ Controllers

Picture	Item No.	Unit Price USD	Specification	Remarks
	SDK55	53	PTZ Controller with 3D (Pan/Tilt,Zoom) Joystick	Set or call the set points and cruise tracks Manually or automatically control RS-485/RS-232 communication Baud rate: 2400-19200Bps Communication distance: Max.1200m Size: 95(H) X 205(L) X 205(W)mm Weight: 2.4Kg
	SDK65	53	PTZ Controller with 3D (Pan/Tilt,Zoom) Joystick	Set or call the set points and cruise tracks Manually or automatically control RS-485/RS-232 communication Baud rate: 2400-19200Bps Communication distance: Max.1200m Size: 95(H) X 205(L) X 205(W)mm Weight: 2.4Kg

Trade Terms:

- 1. Price Term: Ex-Factory, Shenzhen, China**
- 2. Payment Term: T/T or West Union**
- 3. Samples: Available after customers pay the charges of sample & freight fees**
- 4. Minimum Order Quantity: At least 10pcs/model after sample order**
- 5. Lead time: 7-15 days**
- 6. Warranty: Two Years after shipment date**

